

HFMED[®]

500S LED | SURGICAL LIGHT WITH PANDENT

• **Precise**

Uniform, homogeneous lighting in surface and deep cavity procedures thanks to 700 500LED's innovative shadow control.

• **Simple**

Our ergonomic, sterile operating concept allows for the simple and flexible control of all functions by the surgical team.

• **Durable**

Almost unlimited LED life expectancy delivers tremendous product reliability and investment protection.

• **Efficient**

Environmentally proactive: low power consumption and durable LEDs minimize the impact on our precious resources.



Official QR code



YOUR IDEAL OPERATING TABLE SUPPLIER
SHANGHAI HUIFENG MEDICAL INSTRUMENT CO.,LTD

Address: NO.885, Qiuxing Road, Nicheng Town, Pudong New Area, Shanghai, China.
Tel: 13764286262
Mob: +86-13764286262
Email: lisa@huifeng-co.com
Web: www.sh-huifeng.com

HFMED[®] CE

500S LED
Shadowless Operating Lamp

HFMED
SHANGHAI HUIFENG MEDICAL INSTRUMENT CO.,LTD



500S LED

500S LED

Adjustable color temperature

Through reliable beam synthesis control technology, the color temperature can be adjusted between 3800K-5000K under the condition that the color rendering index is 93. Surgeons can adjust the color temperature according to their own habits or different surgical sites to achieve the ideal tissue contrast and achieve the best tissue resolution.



700/500LED one key low light (Endoscope)

The operation shadowless lamp is equipped with a one-key low light (endoscope) lighting mode, which is convenient for the surgeon to quickly switch from the general mode. It does not interfere with the doctor's field of vision and the observation of tissues during endoscopic surgery.



General mode

700LED Endoscope Mode

500LED Endoscope Mode

Main Technical Data

500S LED <small>Surgical Light With Pendant</small>	
Illuminance	≥140,000Lux
Colour temperature	3800±500K 4400±500K 5000±500K
Colour reduction index(Ra)	95
Illuminance depth	≥1400mm
Total irradiance	534W/ m ²
Size of light field	250-300mm
Service life of illuminant	50,000h
Power supply voltage	AC110-240V 50/60Hz
Lowest height of installation	2900mm
Total power consumptio	60W
Total LED bulb quantity	72pcs(12*6)
LED bulb	3.3mW/m ² lx
ENDO	YES